



Pro Form Products Ltd.
604 McGeachie Drive
Milton; Ontario; L9T 3Y5
Canada

PRODUCT: PF 539 AIR INTAKE CLEANER
Section 01: Chemical product and company identification

Product name..... PF 539 AIR INTAKE CLEANER
 Manufactured for..... Pro Form Products Ltd.
 604 McGeachie Drive
 Milton, Ontario L9T3Y5
 Tel (905) 878-4990 Fax (905) 878-1189
 24 hour emergency number..... IN CANADA CALL CANUTEC (613) 996-6666-IN THE UNITED STATES CALL
 CHEMTREC (800) 424-9300.
 Material use..... Cleaning solution. This product should not be used for any other purpose other than the
 ones described in this section.
 Chemical family..... Mixture.
 Preparation date..... November 26, 2014.
 Hazard rate
 NFPA rating..... Health: 2 Fire: 4 Reactivity: 0.
 HMIS..... H: 2 F: 4 R: 0.

Section 02: Hazards identification


Signal Word..... DANGER.
 Hazard Classification..... Flammable Aerosol 1. Flammable Liquid 2. Gas under pressure: Compressed Gas. Eye
 Irritant 2. Skin Irritant 2. STOT SE 3. Reproductive 2. STOT RE 2.
 Hazard Description..... H222 Extremely flammable aerosol . H225 Highly flammable liquid and vapour. H280
 Contains gas under pressure; may explode if heated. H315 Causes skin irritation. H319
 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause
 drowsiness or dizziness. H361 This product contains ingredients that are suspected of
 damaging fertility or the unborn child. H373 May cause damage to the liver and kidneys
 through prolonged or repeated contact.
 Precautionary Statements..... P201 Obtain special instructions before use. P202 Do not handle this product until all
 safety instructions have been read and understood. P210 Keep away from heat, sparks,
 open flames and hot surfaces. No smoking. P211 Do not spray on an open flame or other
 ignition sources. P233 Keep container tightly closed. P240 Ground and bond container and
 receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking
 tools. P243 Take precautionary measures against static discharge. P251 Do not pierce or
 burn container, even after use. P260 Do not breathe mist, vapours, or spray. P261 Avoid
 breathing mists, vapours and sprays. P264 Wash hands thoroughly after handling. P271
 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye
 protection.
 Response P302 + P352 - If on skin: wash with plenty of water. . P303 + P361 + P353 If on skin or in
 hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use
 safety shower . P304 + P340 - If inhaled remove person to fresh air and keep comfortable
 for breathing. P305 + P351 + P338 If in eyes rinse cautiously with water for several
 minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical
 help arrives. P308 + P313 If exposed or concerned, get medical advice/attention. P312 Call
 a poison center/doctor if you feel unwell. P314 - Get medical advice/attention if you feel
 unwell. P321 - Consult with a doctor or poison control centre if skin is itchy or a skin rash
 develops or you feel unwell. P332 + P313 - If skin irritation occurs get medical attention or
 advice. P337 + P313 - If eye irritation persists get medical attention. P362 + P364 - Take
 off contaminated clothing and wash before reuse. P370 + P378 In case of fire - use dry
 chemical powder, CO2 or 6% foam.
 Storage..... P403 + P233 Store in a well ventilated area. Keep container tightly closed. P403 + P235
 Store in well ventilated area. Keep cool. P405 Store locked up. P410 Protect from sunlight.
 P412 Do not expose to temperature exceeding 50C / 122F.
 Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Section 03: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS #	Wt. %
TOLUENE	108-88-3	15-40
XYLENE	1330-20-7	10-30
ACETONE	67-64-1	10-30

PRODUCT: PF 539 AIR INTAKE CLEANER**Section 03: COMPOSITION/INFORMATION ON INGREDIENTS**

DIACETONE ALCOHOL	123-42-2	7-13
PROPANE	74-98-6	7-13
ISOBUTANE	75-28-5	7-13

Section 04: First aid measures

Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
Skin contact.....	Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.
Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	Do not induce vomiting. If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
Additional information.....	Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

Section 05: Fire fighting measures

Extinguishing media.....	"Alcohol" foam, CO2, dry chemical. In cases of larger fires, water spray should be used.
Hazardous combustion products.....	Oxides of carbon (CO, CO2).
Special fire fighting procedures.....	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control. Heat will cause pressure buildup and may cause explosive rupture.

Section 06: Accidental release measures

Leak/spill.....	Ventilate. Eliminate all sources of ignition. Contain the spill. Avoid all personal contact. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. Evacuate all non-essential personnel. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%).
-----------------	---

Section 07: Handling and storage

Handling procedures.....	Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid breathing vapours or mist. Ground handling equipment. Handle and open container with care. Employees should wash hands and face before eating or drinking. Keep away from heat, sparks, and open flame.
Storage needs.....	Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight.

Section 08: Exposure controls / personal protection

Protective equipment	
Eye/type.....	Liquid chemical goggles.
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.
Gloves/ type.....	Chemical resistant gloves.
Clothing/type.....	Wear adequate protective clothes.
Footwear/type.....	Safety boots per local regulations.
Other/type.....	Emergency showers and eye wash stations should be available.
Ventilation requirements.....	Local exhaust at points of emission.
Exposure limits	

Ingredients	TWA	ACGIH TLV		PEL	OSHA PEL		REL	NIOSH
		STEL			STEL			
TOLUENE	20 ppm	Not established		200 ppm	500 ppm	10 minutes	100 ppm	STEL 150 ppm

PRODUCT: PF 539 AIR INTAKE CLEANER**Section 08: Exposure controls / personal protection**

Ingredients	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL NIOSH
XYLENE	100 ppm	150 ppm	100 ppm	Not established	Not established
ACETONE	500 ppm	750 ppm	1,000 ppm	Not established	250 ppm
DIACETONE ALCOHOL	50 ppm	Not established	50 ppm	Not established	50 ppm
PROPANE	1,000 ppm	Not established	1,000 ppm	Not established	1,000 ppm
ISOBUTANE	Not established	Not established	Not established	Not established	800 ppm

Section 09: Physical and chemical properties

Physical state.....	Aerosol.
Colour.....	Clear to pale yellow.
Odour.....	Hydrocarbon odour.
Odour threshold (ppm).....	No data.
Vapour pressure (mm Hg).....	70 @ 20c.
Vapour density (air=1).....	>1.
pH.....	Not applicable.
Specific gravity.....	Liquid: 0.82lb/usg (0.10g/mL) - Aerosol: 0.76lb/usg (0.09g/mL).
Freezing point (deg C).....	No data.
Solubility.....	Partially.
Boiling point (deg C).....	56°C.
Evaporation rate.....	Greater than n-butyl acetate.
Flash point (deg C), method.....	-17.0 °C Closed Cup. Aerosol flame projection > 100 cm.
Auto ignition temperature (deg C).....	No data.
Upper flammable limit (% vol).....	13.
Lower flammable limit (% vol).....	1.2.
Coefficient of water/oil distribution.....	No data.
% Volatile by volume.....	97.
VOC.....	7.17 lb/gal - 859 g/L.
Viscosity.....	Not available.

Section 10: Stability and reactivity

Stability.....	Stable at normal temperatures and pressures.
Reactivity conditions.....	Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
Incompatibility.....	Keep away from heat. Incompatible with strong oxidizers.
Hazardous products of decomposition.....	By fire: Dense black smoke. Oxides of carbon (CO,CO2).
Hazardous polymerization.....	Hazardous polymerization will not occur.

Section 11: Toxicological information

Route of entry	Eye contact. Skin contact. Inhalation.
Skin contact.....	Can cause moderate irritation, defatting and dermatitis.
Skin absorption.....	May be harmful if absorbed through the skin.
Eye contact.....	Can cause redness, irritation, tissue destruction.
Inhalation (acute).....	Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, vomiting and unconsciousness.
Inhalation (chronic).....	Chronic exposure to organic solvent vapors have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties.
Ingestion.....	May be harmful or fatal if swallowed. Swallowing causes inebriation, headache, vomiting, leading to severe illness, blindness, even death. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.
Effects of chronic exposure.....	Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated skin contact may cause drying or cracking of skin. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal .
Carcinogenicity of material.....	None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.
Reproductive effects.....	Toluene is known by the State of California to cause adverse fetal developmental effects.
Toxicological Data	

Ingredients	LC50-inh, rat	LD50-Oral,rat
TOLUENE	8000 ppm rat inhalation	5,000 mg/kg rat oral; 12,124 mg/kg rabbit dermal

PRODUCT: PF 539 AIR INTAKE CLEANER**Section 11: Toxicological information**

Ingredients	LC50-inh, rat	LD50-Oral, rat
XYLENE	6350 ppm 4 hours rat	>3523 mg/kg rat oral
ACETONE	50,100 mg/m ³ 8 hours rat inhalation	5,800 mg/kg rat oral
DIACETONE ALCOHOL	No data	4000 mg/kg oral rat 14.5 mL/kg dermal rabbit
PROPANE	>1,464 mg/L 15 minutes rat	No data
ISOBUTANE	52 mg/L 1 hour mouse	No data

Section 12: Ecological information

Environmental..... Do not allow to enter waters, waste water or soil.
 Biodegradability..... No data.

Section 13: Disposal considerations

Waste disposal..... This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty. Do not heat or cut empty containers with electric or gas torch. Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.

Section 14: Transport information

TDG Classification (Road)..... UN1950 - AEROSOLS, flammable - Class 2.1 - This product meets limited quantity exemption when shipped in containers less than 1 Litre.
 DOT Classification (Road)..... UN1950 - AEROSOLS, flammable - Class 2.1 - Ltd Qty (1 Liter/0.26 Gallons).
 IATA Classification (Air)..... UN1950 - AEROSOLS, flammable - Class 2.1 - Limited Quantity.
 IMDG Classification (Marine)..... UN1950 - AEROSOLS - Class 2.1 - EmS: F-D, S-U - Limited Quantity.
 Marine Pollutant..... Potential marine pollutant.

Section 15: Regulatory information

WHMIS classification..... A. B5. D2A. D2B.
 CEPA status..... On Domestic Substances List (DSL).
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous substances None.
 Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
 Section 313..... Toluene. Xylene.
 EPA hazardous air pollutants (HAPS) Toluene. Xylene.
 40CFR63
 TSCA inventory status..... All components are listed.
 California Proposition 65..... This product contains Toluene known to the State of California to cause (developmental) reproductive toxicity.

Section 16: Other information

Prepared by: REGULATORY AFFAIRS.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
 Disclaimer:..... Regulatory Affairs